

Oil in Water Analyzer

MS1200



MS1200

Oil in Water Analyzer

Continuous Water Intake Protection



The **MS1200 Oil in Water and Pollution Analyzer** is designed to protect drinking water treatment plants from pollution events at the raw water intake. These events can result in expensive filter replacement and clean-up operations and may also affect the **quality of drinking water** produced.

In addition, the system can be used for a wide range of surface water, ground water and industrial water applications.

The MS1200 utilizes a contactless measurement technique, sensing headspace gases to provide a measurement system that is **not affected by the turbidity** of the water and has very low maintenance requirements.

The instrument is accurate to low ppb concentrations for a **wide range** of compounds, including fuel oils, PAH, VOCs and BTEX compounds.

Its continuous measurement mode provides immediate information on pollution levels allowing a rapid response to any event.

It is available with a **standard display or touch screen** interface.

- ✓ Monitors for pollution events
- ✓ No sensor contact with water
- ✓ Low maintenance, no sensor cleaning
- ✓ Not affected by turbidity
- ✓ High sensitivity, ideal for boreholes



Applications

- Monitoring of water abstraction points
- Monitoring of **drain and storm water** systems
- Detection of **fuel pollution** in surface water
- Detection of VOC breakthrough in **carbon beds**
- **Reverse Osmosis membrane** protection
- Protection of **desalination plants**

Installation

Installation is a **simple process** and consists of connecting the instrument to power and the water source to be monitored. Setup uses a user friendly app running on a laptop PC or the touchscreen interface.



CASE STUDY

The Problem

In 2013 a petrochemical plant in the UK caused an oil spill into a river. The local water company extracted water from the river to supply a nearby town and had no water monitoring in place. This meant that the extraction point experienced **high levels of hydrocarbon contamination**.

The Consequences

The hydrocarbon pollution led to **significant disruption** for customers because of the halt in production. The water company also faced high costs for the clean-up. The disruption to supply led to negative PR, on a local and national level, questioning the quality of the water.

The Solution

The water company approached Multisensor Systems looking for a **reliable solution**. After some discussions, the WTP purchased an MS1200 Oil in Water Analyzer.

The MS1200 is now installed in an outbuilding at around 70 m from the extraction point. Water is analyzed for hydrocarbons and VOCS and, if there's an increased level, an **alarm is triggered and appropriate action is taken**.

Since the installation the system has protected the water plant on **several occasions** from significant pollution events.

“...without the MS1200 it is far more likely that we'll be prosecuted and make the national news.”

TECHNICAL SPECIFICATION

PARAMETER	OPERATIONAL REQUIREMENTS		NOTES
	<i>Minimum</i>	<i>Maximum</i>	
Supply Voltage	90 V AC	240 V AC	50 Hz or 60 Hz
Power Consumption: Standard Version Touch Screen Version		15 W 45 W	Typical 10 W during operation Typical 20 W during operation
Water Supply	2 l/min / 0.52 US gpm		Clear PVC tank
Water Pressure	4.0 bar / 58 psi		
Working Temp: Ambient	0 °C / 32 °F	40 °C / 104 °F	
Working Temp: Water	1 °C / 34 °F	40 °C / 104 °F	
Sampling Period	Continuous		
Detection Range	1 ppb	3000 ppb	Measured against Toluene standard. For calibration using other compounds contact Multisensor Systems
Repeatability	-2%	+2%	200 ppb sample measured using standard 1.5 l solution (Water plus Tol- uene dissolved in DMSO) in glass 2.5 l Winchester type bottle using magnetic stirrer at 20 °C / 68 °F
Accuracy	-10%	+10%	
Display Range (Default)	0 ppb	1000 ppb	Configurable on commissioning
Analog Output	4 mA	20 mA	Scalable to range required, max load 900 Ω
Analog Output Isolation	400 V DC		
Relay Voltage		50 V	3x, Alarm 1, Alarm 2 and Fault Relays with NO and NC contacts
Relay Current		5 A	
User Interface	USB-A to PC		Using Multisensor Software provided
Flow Limit Switch	Contacts closed if flow below set point		Option available on request
Instrument Case	IP65 / NEMA 4X		Coated Mild Steel
Sample Tank Material	Stainless Steel		Optional: PVC
Weight	25 kg / 55 lbs		
Dimensions	1170 x 490 x 300 mm 46 x 19.2 x 11.8 inches		Mounted on 2 separate PVC back- boards

Service and consumables

Every 6 Months: Air Filters

Every 12 Months: Air Pump



multisensor
systems
sensing measuring protecting

www.multisensorsystems.com
e: info@multisensorsystems.com
p: +44 (0)161 491 5600

Multisensor Systems is a developer and supplier of Water and Gas Analyzers specialising in oil in water, hydrocarbon analyzers, oil in water detectors, THM Analyzers and Ammonia Analyzers based in the United Kingdom.

The contents of this publication are provided to you "as is" without warranty of any kind, and are subject to change without notice. Multisensor systems does not assume any responsibility or liability for any damage, whether direct or indirect, relating to the use of this publication.

Multisensor Systems Ltd., Alexandra Court, Carrs Road, Cheadle, SK8 2JY, United Kingdom